


NA69 Series



select	Inquiry Designation		Principal Dimensions						Cr	Cor	Fatigue Load Cu	Limiting Speed nG	Reference Speed nB	Weight
			d	D	B	F	r	s						
NA6904	20 mm	37 mm	30 mm	25 mm	0,3 mm	1 mm	40500 N	51000 N	9100 N	17200 U/min	9200 U/min	141 g		
NA6901	12 mm	24 mm	22 mm	16 mm	0,3 mm	1 mm	18100 N	21600 N	3800 N	23600 U/min	13900 U/min	46 g		
NA6902	15 mm	28 mm	23 mm	20 mm	0,3 mm	1 mm	19500 N	25500 N	4450 N	21600 U/min	11700 U/min	63,6 g		
NA6903	17 mm	30 mm	23 mm	22 mm	0,3 mm	1 mm	21100 N	29000 N	5100 N	20600 U/min	10500 U/min	72 g		
NA69/22	22 mm	39 mm	30 mm	28 mm	0,3 mm	0,5 mm	42000 N	55000 N	9900 N	16100 U/min	8500 U/min	150 g		
NA6906	28mm	45 mm	30 mm	32 mm	0,3 mm	1 mm	45500 N	63000 N	11400 N	13400 U/min	7000 U/min	182 g		
NA69/28	25 mm	42 mm	30 mm	30 mm	0,3 mm	1 mm	44000 N	59000 N	10600 N	14600 U/min	7700 U/min			
NA69/32	30 mm	47 mm	30 mm	35 mm	0,3 mm	1 mm	49000 N	71000 N	12900 N	12700 U/min	6400 U/min	192 g		
NA6907	32 mm	52 mm	36 mm	40 mm	0,6 mm	0,5 mm	53000 N	82000 N	15100 N	11700 U/min	6500 U/min	288 g		
NA6908	35 mm	55 mm	36 mm	42 mm	0,6 mm	0,5 mm	54000 N	86000 N	15900 N	10900 U/min	6100 U/min	310 g		
NA6909	45 mm	68 mm	40 mm	52 mm	0,6 mm	0,5 mm	79000 N	127000 N	21400 N	8700 U/min	4850 U/min	495 g		
NA6910	50 mm	72 mm	40 mm	58 mm	0,6 mm	0,5 mm	82000 N	139000 N	23400 N	8000 U/min	4400 U/min	515 g		
NA6911	55 mm	80 mm	45 mm	63 mm	1 mm	1,5 mm	102000 N	176000 N	30000 N	7300 U/min	4100 U/min	780 g		
NA6912	60 mm	85 mm	45 mm	68 mm	1 mm	1,5 mm	106000 N	191000 N	32500 N	6800 U/min	3750 U/min	808 g		
NA6913	65 mm	90 mm	45 mm	72 mm	1 mm	1,5 mm	108000 N	198000 N	33500 N	6300 U/min	3550 U/min	833 g		
NA6914	70 mm	100 mm	54 mm	80 mm	1 mm	1 mm	145000 N	265000 N	47500 N	5800 U/min	3400 U/min	1340 g		
NA6915	75 mm	105 mm	54 mm	85 mm	1 mm	1 mm	147000 N	275000 N	49500 N	5400 U/min	3200 U/min	1450 g		
NA6916	80 mm	110 mm	54 mm	90 mm	1 mm	1 mm	153000 N	300000 N	53000 N	5200 U/min	3000 U/min	1522 g		
NA6917	85 mm	120 mm	63 mm	100 mm	1,1 mm	1 mm	188000 N	400000 N	71000 N	4800 U/min	2850 U/min	2200 g		
NA6918	90 mm	125 mm	63 mm	105 mm	1,1 mm	1 mm	195000 N	425000 N	74000 N	4550 U/min	2700 U/min	2310 g		
NA6919	95 mm	130 mm	63 mm	110 mm	1,1 mm	1mm	197000 N	440000 N	76000 N	4350 U/min	2600 U/min	2500 g		