


# NA48 Series



| select  | Inquiry | Designation | Principal Dimensions |        |        |        |           |           | Cr        | Cor        | Fatigue Load Cu | Limiting Speed nG | Reference Speed nB | Weight |
|---------|---------|-------------|----------------------|--------|--------|--------|-----------|-----------|-----------|------------|-----------------|-------------------|--------------------|--------|
|         |         |             | d                    | D      | B      | F      | r         | s         |           |            |                 |                   |                    |        |
| NA4822  | 110 mm  | 140 mm      | 30 mm                | 120 mm | 1 mm   | 0,8 mm | 106000 N  | 216000 N  | 36000 N   | 3900 U/min | 2300 U/min      | 1080 g            |                    |        |
| NA4824  | 120 mm  | 150 mm      | 30 mm                | 130 mm | 1 mm   | 0,8 mm | 112000 N  | 239000 N  | 39000 N   | 3650 U/min | 2090 U/min      | 1170 g            |                    |        |
| NA4826  | 130 mm  | 165 mm      | 35 mm                | 145 mm | 1,1 mm | 1 mm   | 134000 N  | 310000 N  | 48500 N   | 3300 U/min | 2000 U/min      | 1810 g            |                    |        |
| NA4828  | 140 mm  | 175 mm      | 35 mm                | 155 mm | 1,1 mm | 1 mm   | 136000 N  | 325000 N  | 50000 N   | 3100 U/min | 1870 U/min      | 1920 g            |                    |        |
| NA 4830 | 150 mm  | 190 mm      | 40 mm                | 165 mm | 1,1 mm | 1,5 mm | 172000 N  | 400000    | 62000     | 2900in     | 1810in          | 2720g             |                    |        |
| NA 4832 | 160 mm  | 200 mm      | 40 mm                | 175 mm | 1,1 mm | 1,5 mm | 181000 N  | 435000 N  | 66000 N   | 2700 U/min | 1680 U/min      | 2890 g            |                    |        |
| NA 4834 | 170 mm  | 215 mm      | 45 mm                | 185 mm | 1,1 mm | 1,5 mm | 209000 N  | 510000 N  | 75000 N   | 2550 U/min | 1610 U/min      | 3960 g            |                    |        |
| NA 4836 | 180 mm  | 225 mm      | 45 mm                | 195 mm | 1,1 mm | 1,5 mm | 219000 N  | 550000 N  | 80000 N   | 2420 U/min | 1490 U/min      | 4200 g            |                    |        |
| NA 4838 | 190 mm  | 240 mm      | 50 mm                | 210 mm | 1,5 mm | 1,5 mm | 255000 N  | 690000 N  | 100000 N  | 2280 U/min | 1350 U/min      | 5610 g            |                    |        |
| NA4840  | 200 mm  | 250 mm      | 50 mm                | 220 mm | 1,5 mm | 1,5 mm | 260000 N  | 720000 N  | 102000 N  | 2150 U/min | 1250 U/min      | 5840 g            |                    |        |
| NA4844  | 220 mm  | 270 mm      | 50 mm                | 240 mm | 1,5 mm | 1,5 mm | 275000 N  | 790000 N  | 110000 N  | 1980 U/min | 1110 U/min      | 6380 g            |                    |        |
| NA4848  | 240 mm  | 300 mm      | 60 mm                | 265 mm | 2 mm   | 2 mm   | 400000 N  | 1080000 N | 1500000 N | 1780 U/min | 960 U/min       | 10000 g           |                    |        |
| NA4852  | 260 mm  | 320 mm      | 60 mm                | 285 mm | 2 mm   | 2 mm   | 415000 N  | 1160000 N | 158000 N  | 1660 U/min | 870 U/min       | 10600 g           |                    |        |
| NA4856  | 280 mm  | 350 mm      | 69 mm                | 305 mm | 2 mm   | 2,5 mm | 510000 N  | 130000 N  | 175000 N  | 1540 U/min | 840 U/min       | 15300 g           |                    |        |
| NA4860  | 300 mm  | 380 mm      | 80 mm                | 330 mm | 2,1 mm | 2 mm   | 700000 N  | 1770000 N | 235000 N  | 1420 U/min | 720 U/min       | 21800 g           |                    |        |
| NA4864  | 320 mm  | 400 mm      | 80 mm                | 350 mm | 2,1 mm | 2 mm   | 710000 N  | 1850000 N | 242000 N  | 1340 U/min | 670 U/min       | 23000 g           |                    |        |
| NA4868  | 340 mm  | 420 mm      | 80 mm                | 370 mm | 2,1 mm | 2 mm   | 730000 N  | 1940000 N | 249000 N  | 1270 U/min | 620 U/min       | 24200 g           |                    |        |
| NA4872  | 360 mm  | 440 mm      | 80 mm                | 390 mm | 2,1 mm | 2 mm   | 740000 N  | 2020000 N | 255000 N  | 1210 U/min | 590 U/min       | 25600 g           |                    |        |
| NA4876  | 380 mm  | 480 mm      | 100 mm               | 415 mm | 2,1 mm | 2 mm   | 1130000 N | 2900000 N | 370000 N  | 1130 U/min | 510 U/min       | 42600 g           |                    |        |