


Shaft diameter from 85 mm to 120 mm



select	Inquiry	Designation	Dimensions mm			Basic Load Rating kN		Fatigue Limit Load kN	Rated Speed r/min		Weight kg
			d	D	B	Cr	Cor		Reference Speed	Limiting Speed	
		61817	85	110	13	19,5	20,8	0,88	12000	7500	0,27
		61917	85	120	18	31,9	30	1,25	11000	7000	0,55
		*16017	85	130	14	35,8	33,5	1,37	11000	6700	0,63
		*6017	85	130	22	52	43	1,76	11000	6700	0,89
		*6217	85	150	28	87,1	64	2,5	9000	5600	1,80
		*6317	85	180	41	140	96,5	3,55	8000	5000	4,25
		6417	85	210	52	174	137	4,75	7000	4500	9,50
		61818	90	115	13	19,5	22	0,915	11000	7000	0,28
		61918	90	125	18	33,2	31,5	1,23	11000	6700	0,59
		*16018	90	140	16	43,6	39	1,56	10000	6300	0,85
		*6018	90	140	24	60,5	50	1,96	10000	6300	1,15
		*6218	90	160	30	101	73,5	2,8	8500	5300	2,15
		*6318	90	190	43	151	108	3,8	7500	4800	4,90
		6418	90	225	54	186	150	5	6700	4300	11,5
		61819	95	120	13	19,9	22,8	0,93	11000	6700	0,30
		61919	95	130	18	33,8	33,5	1,43	10000	6300	0,61
		*16019	95	145	16	44,8	41,5	1,63	9500	6000	0,89
		*6019	95	145	24	63,7	54	2,08	9500	6000	1,20
		*6219	95	170	32	114	81,5	3	8000	5000	2,60

Shaft diameter from 85 mm to 120 mm

*6319	95	200	45	159	118	4,15	7000	4500	5,65
61820	100	125	13	19,9	24	0,95	10000	6300	0,31
61920	100	140	20	42,3	41	1,63	9500	6000	0,83
*16020	100	150	16	46,2	44	1,73	9500	5600	0,91
*6020	100	150	24	63,7	54	2,04	9500	5600	1,25
*6220	100	180	34	127	93	3,35	7500	4800	3,15
6320	100	215	47	174	140	4,75	6700	4300	7,00
61821	105	130	13	20,8	19,6	1	10000	6300	0,32
61921	105	145	20	44,2	44	1,7	9500	5600	0,87
*16021	105	160	18	54	51	1,86	8500	5300	1,20
*6021	105	160	26	76,1	65,5	2,4	8500	5300	1,60