


Shaft diameter from 360 mm to 1500 mm



select	Inquiry Designation		Dimensions mm			Basic Load Rating kN		Fatigue Limit Load kN	Rated Speed r/min		Weight kg
			d	D	B	Cr	Cor		Reference Speed	Limiting Speed	
61872MA	360	440	38	182	285	6,1	2600	2200	12,0		
61972MA	360	480	56	291	450	9,15	2600	2000	28,0		
16072MA	360	540	57	351	550	11	2400	1900	49,0		
6072M	360	540	82	462	735	15	2400	1900	64,5		
61876MA	380	480	46	242	390	8	2400	2000	20,0		
61976MA	380	520	65	338	540	10,8	2400	1900	40,0		
16076MA	380	560	57	377	620	12,2	2200	1800	51,0		
6076M	380	560	82	462	750	14,6	2200	1800	67,5		
61880MA	400	500	46	247	405	8,15	2400	1900	20,5		
61980MA	400	540	65	345	570	11,2	2200	1800	41,5		
6080M	400	600	90	520	865	16,3	2000	1700	87,5		
61884MA	420	520	46	251	425	8,3	2200	1800	21,5		
61984MA	420	560	65	351	600	11,4	2200	1800	43,0		
6084M	420	620	90	507	880	16,3	2000	1600	91,5		
61888MA	440	540	46	255	440	8,5	2200	1800	22,5		
61988MA	440	600	74	410	720	13,2	2000	1600	60,5		
6088M	440	650	94	553	965	17,6	1900	1500	105		
61892MA	460	580	56	319	570	10,6	2000	1600	35,0		
61992MA	460	620	72	423	750	13,7	1900	1600	62,5		
6092MB	460	680	100	582	1060	19	1800	1500	120		
61896MA	480	600	56	325	600	10,8	1900	1600	36,5		

Shaft diameter from 360 mm to 1500 mm

61996MA	480	650	78	449	815	14,6	1800	1500	74,0
6096MB	480	700	100	618	1140	20	1700	1400	125
618/500MA	500	620	56	332	620	11,2	1800	1500	40,5
619/500MA	500	670	78	462	865	15	1700	1400	77,0
60/500N1MAS	500	720	100	605	1140	19,6	1600	1300	135
618/530MA	530	650	56	332	655	11,2	1700	1400	39,5
619/530MA	530	710	82	488	930	15,6	1600	1300	90,5
60/530N1MAS	530	780	112	650	1270	20,8	1500	1200	185
618/560MA	560	680	56	345	695	11,8	1600	1300	42,0