



select	Inquiry Designation		Dimensions in mm							Details				weight	Cr COr
			d	D	B	seal	C	bk	r1s min.	r2s min.	da max.	Da min.			
GE5-PW	5	13	8	-	6 mm	11,112 mm	0,3 mm	0,3 mm	7,7 mm	9,8 mm	0,006 kg	6000 N	15000 N		
GE6-PW	6	16	9	-	6 mm	12,7 mm	0,3 mm	0,3 mm	8,9 mm	11,5 mm	0,01 kg	7650 N	19300 N		
GE8-PW	8	19	12	-	9 mm	15,875 mm	0,3 mm	0,3 mm	10,3 mm	14 mm	0,019 kg	12900 N	32000 N		
GE10-PW	10	22	14	-	10 mm	19,05 mm	0,3 mm	0,3 mm	12,9 mm	17 mm	0,027 kg	18000 N	45000 N		
GE12-PW	12	26	16	-	12 mm	22,225 mm	0,3 mm	0,3 mm	15,4 mm	19,5 mm	0,043 kg	24000 N	60000 N		
GE14-PW	14	28	19	-	13 mm	25,4 mm	0,3 mm	0,3 mm	16,8 mm	22,5 mm	0,054 kg	31000 N	76500 N		
GE16-PW	16	32	21	-	15 mm	28,575 mm	0,3 mm	0,3 mm	19,3 mm	25,5 mm	0,079 kg	39000 N	96500 N		
GE18-PW	18	35	23	-	16 mm	31,75 mm	0,3 mm	0,3 mm	21,8 mm	28,5 mm	0,1 kg	47500 N	118000 N		
GE20-PW	20	40	25	-	18 mm	34,925 mm	0,3 mm	0,6 mm	24,3 mm	31,5 mm	0,15 kg	57000 N	140000 N		
GE22-PW	22	42	28	-	20 mm	38,1 mm	0,3 mm	0,6 mm	25,8 mm	34 mm	0,18 kg	68000 N	170000 N		
GE25-PW	25	47	31	-	22 mm	42,85 mm	0,3 mm	0,6 mm	29,5 mm	38,5 mm	0,24 kg	85000 N	212000 N		
GE30-PW	30	55	37	-	22 mm	42,85 mm	0,3 mm	0,6 mm	29,5 mm	38,5 mm	0,24 kg	85000 N	212000 N		