



select	Inquiry	Designation	Dimensions in mm							Details				weight	Cr COr
			d	D	B	seal	C	bk	r1s min.	r2s min.	da max.	Da min.			
GE5-PB	5	13	8	-	6 mm	11,112 mm	0,3 mm	0,3 mm	7,7 mm	9,8 mm	0,006 kg	3250 N	8500 N		
GE6-PB	6	16	9	-	6 mm	12,7 mm	0,3 mm	0,3 mm	8,9 mm	11,5 mm	0,01 kg	4300 N	10800 N		
GE8-PB	8	19	12	-	9 mm	15,875 mm	0,3 mm	0,3 mm	10,3 mm	14 mm	0,018 kg	7200 N	18000 N		
GE10-PB	10	22	14	-	10 mm	19,05 mm	0,3 mm	0,3 mm	12,9 mm	17 mm	0,027 kg	10000 N	25000 N		
GE12-PB	12	26	16	-	12 mm	22,225 mm	0,3 mm	0,3 mm	15,4 mm	19,5 mm	0,043 kg	13400 N	33500 N		
GE14-PB	14	28	19	-	13 mm	25,4 mm	0,3 mm	0,3 mm	16,8 mm	22,5 mm	0,055 kg	17000 N	43000 N		
GE16-PB	16	32	21	-	15 mm	28,575 mm	0,3 mm	0,3 mm	19,3 mm	25,5 mm	0,08 kg	21600 N	54000 N		
GE18-PB	18	35	23	-	16 mm	31,75 mm	0,3 mm	0,3 mm	21,8 mm	28,5 mm	0,1 kg	26000 N	66500 N		
GE20-PB	20	40	25	-	18 mm	34,925 mm	0,3 mm	0,6 mm	24,3 mm	31,5 mm	0,15 kg	31500 N	80000 N		
GE22-PB	22	42	28	-	20 mm	38,1 mm	0,3 mm	0,6 mm	25,8 mm	34 mm	0,18 kg	38000 N	96500 N		
GE25-PB	28	47	31	-	22 mm	42,85 mm	0,3 mm	0,6 mm	29,5 mm	38,5 mm	0,24 kg	47500 N	118000 N		
GE30-PB	30	55	37	-	25 mm	50,8 mm	0,3 mm	0,6 mm	34,8 mm	46 mm	0,38 kg	64000 N	160000 N		